

86301 Rugged MINI VoIP

Aqeri 86301 is a rugged compact fanless Voice over IP (VoIP) for harsh environments. The VoIP is a Gateway-Router that supports up to for FXO or FXS connections. The VoIP is designed with a wide input voltage range which makes the unit usable in vehicles. An internal climate control system makes the unit usable in extremely low and high temperature environments. The chassis is fully sealed for protection against dust and corrosive elements. The full aluminum design stands for low radiation and high noise immunity.



TECHNICAL DATA

Features:	Gateway-Router supports four FXO or FXS connections
Dimensions:	220 x 300 x 65,8 mm (WxDxH)
Weight:	2,5 kg
Color:	Military green, optional any color
Power requirements:	9-36 VDC
Connectors:	4x RJ11 FXO/FXS, 1x fiber Multimode/Singlemode, 1x RJ45 Ethernet, 1x Console (D-SUB), 1x DC in 97B-3100A10SL-3P-HD,
Mounting:	Stand alone, 19" rack single or together in pairs, wall mount
Temperature:	Operating Temp -20°C to +55°C, Storage -40°C to +70°C
Humidity:	5% to 95% non condensing
Vibration:	10-500Hz rms=1.04g
Shock:	Operating 10g, 11ms ½ sine wave pulse
Altitude:	Operating 10 000 feet, Storage 30 000 feet
Designed to fulfill:	MIL-STD-810G, MIL-STD-461F, IP54

Other specifications to be quoted upon customers request.